




linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



REVISION RECORD				
REV.	DESCRIPTION	ECN NO.	APPROVE	DATE
A	新发行		YXW	2021. 2. 25

UL/CUL 技术 参数					
UL/CUL Technical Data					
等 级	Use Group	B	C	D	
额定电压	Rated Voltage	[V]	300	-	300
额定电流	Rated Current	[A]	10	-	10
接线范围	Wire Range	24-12			
单/多芯线	Solid/Stranded				[AWG]
耐电压	Withstanding Voltage	AC1600V/1Min			
IEC 技术参数					
IEC Technical Data					
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	
额定电压	Rated Voltage	[V]	-	320	630
额定电流	Rated Current	[A]	-	15	15
额定冲击电压	Impulse withstand voltagea	[KV]	-	4.0	4.0
导线截面积	Conductor cross section	2.5			
硬质/柔性导线	Solid/ flexible				[mm ²]
材 料					
绝缘材料	Insulation Material	热塑性材料 Thermoplastic			
导体材料	Contact Material	铜合金 Copper alloy			
导体表面镀层	Contactive Coating	镀镍 Ni plated			
一般参数 Other Data					
间距 Pitch	[mm]	5.0			
极数 Poles	[P]	2-24			
剥线长度 Stripping Length	[mm]	7-8			
螺丝 Screw/扭矩 Torque(Max)	[N.m]	M2.5/0.4			
工作温度 Operating temperatur	[°C]	-40~+105			
引针尺寸 Pin Dimensions	[mm]	-			
PCB板孔径 PCB Hole Diameter	[mm]	-			

DES.	CLB	DATE	2021. 2. 25	单位/UNITS	MM	时间/SIZE	A4	比例/SCALE	1:1	第三视角/THIRDANGLEPROJECTION		版本/REV	A
CHK.	LF	DATE	2021. 2. 25	宁波市旭骋电子有限公司 NINGBOSHI XUCHENG ELECTRONIC CO., LTD								名称/TITLE	XC2EDGKBM-5. 00
APP.	YXW	DATE	2021. 2. 25										